

THALER Yard loader 1220

Eu-Emission standard V without DOC/DPF

19 hp




Engine	3-cylinder Yanmar diesel engine 14,6 KW (19hp)
Displacement	900 ccm - 3000 rpm
Cooling	water cooler, oil cooler
Drive	hydrostatic transmission with automotive control / 230 bar
Transmission	4 wheel hub motors
Working hydraulic	approx. 33l/min, 160 bar
Speed	aprox. 16 km/h, (1 speed)
Battery	12V - 45AH
Diesel tank	25l
Hydraulic oil tank	25l
Brake	drum Brake acting on rear wheels

available 2022

Standard:

- CE-Approval
- High tensile Thaler articulated pendulum joint
- Third hydraulic control circuit (DN12 hose on lifting arm), hydraulic quick hitch
- Multi-functional joystick, Single-lever-control with floating position in the lifting ram
- Change of direction (rocker switch) on joystick
- Optimized parallel-motion
- Thaler inch-pedal
- Mechanically suspended comfort seat with security belt and operator restraint system conform to latest CE-Machinery directives
- Fops-Rops-Cage
- 2 LED-working lights (each 1150lm) mounted on the cage (1 at the front, 1 at the back)
- Convenient access, no drive shaft hump
- Great visibility through intelligent front carriage design
- Solid steel platform tilts back for perfect accessibility for maintenance
- Easily accessible lubrication points
- Large combined oil-water- cooler
- Protective tubes on the hydraulic hoses
- Battery disconnecter on the outside
- Quick coupling system Thaler Small with hydraulic locking by three-way-valve
- Z-Kinematic

Your small help for:

Transport	Bale transport	Muck out the stable	Sweeping
			
Mowing	Construction work	Pushing	Slurry pushing
	